

A6 C6 B8 Style Guide

Affix STāSIS badges and decals to the Signature Series automobiles according to the following guidelines:

Front Plate Delete STāSIS Sticker

Apply STāSIS sticker centered on the front plate delete panel. (See image below.) Depending on the size of the sticker (small or large), measure the recommended distance from the intersection of the two middle Audi rings. See image:



Rear Deck-lid STāSIS Badge

Affix the STāSIS badge to the rear deck-lid on the passenger (right) side.

1. Remove the existing "3.0T" badge (keep the "quattro" badge to use as a reference, to be removed on step 4) by gently applying dental floss in a sawing motion to separate the adhesive behind the badge.
2. Clean surface of all dirt and adhesive material. Place the STāSIS badge so that the name "STāSIS" is centered over the word "Quattro." The STāSIS badge should be 1/4" above the Quattro badge.
3. Mock up badge in the proper location before removing adhesive backing, if the badge does not sit flat against the contour of the deck-lid, bend badge by hand to match the contour of the surface.
4. After applying STāSIS badge, remove the "quattro" badge with dental floss and clean off adhesive.




A6 C6 B8 Style Guide

Side Marker STāSIS Signature Series Side Badge

Apply side badges on the upper corners of the front fender panels.

1. Remove any existing OEM badges by gently applying dental floss in a sawing motion to separate the adhesive behind the badge.
2. Clean surfaces of all dirt and adhesive material.
3. Align the Signature Series badge based on the following measurements.
4. Ensure that the badge is parallel to the ground. Follow these guidelines for both sides of the vehicle.



Tire Sticker

The tire sticker supplied is to be installed over the existing tire sticker located on the B-pillar of the driver's side of the vehicle.

1. Clean the existing sticker area and apply the new tire sticker directly over the existing sticker.